



SN型基本系列参数表

基本型号	外形尺寸			安装孔尺寸						结构尺寸			齿轮参数			内齿参数		质量
	D	d	H	D ₁	D ₂	n	通孔	螺纹孔		n ₁	H ₁	h	b	x	m	da	Z	Kg
							A型	B.C.D型										
							φ	φ	T									
SN□1000.20	1146	844	128	1094	894	28	26	M24	45	4	4	10	98	0.5	10	790	80	418
SN□1120.20	1266	964	128	1214	1014	32	26	M24	45	4	4	10	98	0.5	12	900	76	470
SN□1250.20	1396	1094	128	1344	1144	36	26	M24	45	4	4	10	98	0.5	12	1032	87	524
SN□1400.20	1546	1240	128	1494	1294	36	26	M24	45	4	4	10	98	0.5	14	1162	84	614
SN□1600.20	1746	1444	128	1694	1494	40	26	M24	45	4	4	10	98	0.5	14	1372	99	686
SN□1600.25	1782	1400	148	1716	1474	32	33	M30	56	4	8	10	110	0.5	14	1330	96	966
SN□1800.25	1982	1600	148	1916	1674	36	33	M30	56	6	8	10	110	0.5	16	1520	96	1096
SN□2000.25	2182	1810	148	2116	1874	44	33	M30	56	6	8	10	110	0.5	16	1728	109	1196
SN□2240.25	2422	2040	148	2356	2114	48	33	M30	56	6	8	10	110	0.5	18	1944	109	1396
SN□2500.25	2682	2310	148	2616	2374	54	33	M30	56	6	8	10	110	0.5	18	2214	124	1532
SN□2240.32	2458	2000	182	2380	2086	40	39	M36	66	6	10	10	130	0.5	18	1908	107	2002
SN□2500.32	2718	2270	182	2640	2346	44	39	M36	66	6	10	10	130	0.5	18	2178	122	2199
SN□2800.32	3018	2560	182	2940	2646	48	39	M36	66	6	10	10	130	0.5	20	2460	124	2526
SN□3150.32	3368	2920	182	3290	2996	56	39	M36	66	8	10	10	130	0.5	20	2820	142	2788
SN□2800.40	3038	2560	220	2960	2638	56	39	M36	66	8	10	10	160	0.5	20	2460	124	3213
SN□3150.40	3388	2910	220	3310	2988	64	39	M36	66	8	10	10	160	0.5	22	2794	128	3683
SN□3550.40	3788	3300	220	3710	3388	72	39	M36	66	8	10	10	160	0.5	22	3190	146	4171
SN□4000.40	4238	3750	220	4160	3838	84	39	M36	66	8	10	10	160	0.5	24	3624	152	4810
SN□3150.50	3416	2870	268	3326	2960	56	45	M42	80	8	14	10	190	0.5	24	2736	115	5072
SN□3550.50	3816	3270	268	3726	3360	64	45	M42	80	8	14	10	190	0.5	24	3144	132	5816
SN□4000.50	4266	3720	268	4176	3810	72	45	M42	80	8	14	10	190	0.5	24	3600	151	6512