

133、134型基本系列参数表

基本型号	外形尺寸			安装孔尺寸						结构尺寸			齿轮参数			内齿参数		质量
	D	d	H	D ₁	D ₂	n	通孔	螺栓孔		n ₁	H ₁	h	b	x	m	da	Z	
							0型	1,2,3型										
							φ	φ	T									
133. 25. 500	634	366	148	598	402	24	18	M16	32	4	138	32	80	0. 5	5	337	68	224
134. 25. 500															6	338. 4	57	
133. 25. 560	694	426	148	658	462	24	18	M16	32	4	138	32	80	0. 5	5	397	80	240
134. 25. 560															6	398. 4	67	
133. 25. 630	764	496	148	728	532	28	18	M16	32	4	138	32	80	0. 5	6	458. 4	77	270
134. 25. 630															8	459. 2	58	
133. 25. 710	844	576	148	808	612	28	18	M16	32	4	138	32	80	0. 5	6	536. 4	90	300
134. 25. 710															8	539. 2	68	
133. 32. 800	964	636	182	920	680	36	22	M20	40	4	172	40	120	0. 5	8	595. 2	75	500
134. 32. 800															10	594	60	
133. 32. 900	1064	736	182	1020	780	36	22	M20	40	4	172	40	120	0. 5	8	691. 2	87	600
134. 32. 900															10	694	70	
133. 32. 1000	1164	836	182	1120	880	40	22	M20	40	5	172	40	120	0. 5	10	784	79	680
134. 32. 1000															12	784. 8	66	
133. 32. 1120	1284	956	182	1240	1000	40	22	M20	40	5	172	40	120	0. 5	10	904	91	820
134. 32. 1120															12	904. 8	76	
133. 40. 1250	1445	1055	220	1393	1107	45	26	M24	48	5	210	50	150	0. 5	12	988. 8	83	1200
134. 40. 1250															14	985. 6	71	
133. 40. 1400	1595	1205	220	1543	1257	45	26	M24	48	5	210	50	150	0. 5	12	1144. 8	96	1300
134. 40. 1400															14	1139. 6	82	
133. 40. 1600	1795	1405	220	1743	1457	48	26	M24	48	6	210	50	150	0. 5	14	1335. 6	96	1520
134. 40. 1600															16	1334. 4	84	



基本型号	外形尺寸			安装孔尺寸						结构尺寸			齿轮参数			内齿参数		质量
	D	d	H	D ₁	D ₂	n	通孔	螺栓孔		n ₁	H ₁	h	b	x	m	da	Z	kg
							0型	1,2,3型										
							φ	φ	T									
133. 40. 1800	1995	1605	220	1943	1657	48	26	M24	48	6	210	50	150	0. 5	14	1531. 6	110	1750
134. 40. 1800															16	1526. 4	96	
133. 45. 2000	2221	1779	231	2155	1845	60	33	M30	60	6	219	54	160	0. 5	16	1702. 4	107	2400
134. 45. 2000															18	1699. 2	95	
133. 45. 2240	2461	2019	231	2395	2085	60	33	M30	60	6	219	54	160	0. 5	16	1926. 4	121	2700
134. 45. 2240															18	1933. 2	108	
133. 45. 2500	2721	2279	231	2655	2345	72	33	M30	60	8	219	54	160	0. 5	18	2185. 2	122	3000
134. 45. 2500															20	2188	110	
133. 45. 2800	3021	2579	231	2955	2645	72	33	M30	60	8	219	54	160	0. 5	18	2491. 2	139	3400
134. 45. 2800															20	2488	125	
133. 50. 3150	3432	2868	270	3342	2958	72	45	M42	84	8	258	65	180	0. 5	20	2768	139	5000
134. 50. 3150															22	2758. 8	126	
133. 50. 3550	3832	3268	270	3742	3358	72	45	M42	84	8	258	65	180	0. 5	20	3168	159	5600
134. 50. 3550															22	3154. 8	144	
133. 50. 4000	4282	3718	270	4192	3808	80	45	M42	84	8	258	65	180	0. 5	22	3116. 8	165	6400
134. 50. 4000															25	3610	145	