



SW型基本系列参数表

基本型号	外形尺寸			安装孔尺寸						结构尺寸			齿轮参数			外齿参数		质量kg
				D ₁	D ₂	n	通孔	螺纹孔					n ₁	H ₁	h	b	x	
	A型	B.C.D型																
	D	d	H				φ	φ	T									
SW□1000.20	1156	854	128	1106	906	28	26	M24	45	4	4	10	98	0.5	10	1210	118	426
SW□1120.20	1280	974	128	1226	1026	32	26	M24	45	4	4	10	98	0.5	12	1344	109	478
SW□1250.20	1410	1104	128	1356	1156	36	26	M24	45	4	4	10	98	0.5	12	1476	120	540
SW□1400.20	1560	1254	128	1506	1306	36	26	M24	45	4	4	10	98	0.5	14	1638	114	626
SW□1600.20	1760	1454	128	1706	1506	40	26	M24	45	4	4	10	98	0.5	14	1834	128	708
SW□1600.25	1790	1418	148	1726	1484	32	33	M30	56	4	8	10	110	0.5	14	1862	130	992
SW□1800.25	2000	1618	148	1926	1684	36	33	M30	56	6	8	10	110	0.5	16	2080	127	1121
SW□2000.25	2190	1818	148	2126	1884	44	33	M30	56	6	8	10	110	0.5	16	2272	139	1211
SW□2240.25	2430	2058	148	2366	2124	48	33	M30	56	6	8	10	110	0.5	18	2520	137	1373
SW□2500.25	2700	2318	148	2626	2384	54	33	M30	56	6	8	10	110	0.5	18	2790	152	1561
SW□2240.32	2464	2022	182	2394	2100	40	39	M36	66	6	10	10	130	0.5	18	2556	139	1968
SW□2500.32	2730	2282	182	2654	2360	44	39	M36	66	6	10	10	130	0.5	18	2826	154	2245
SW□2800.32	3040	2582	182	2954	2660	48	39	M36	66	6	10	10	130	0.5	20	3140	154	2566
SW□3150.32	3380	2932	182	3304	3010	56	39	M36	66	8	10	10	130	0.5	20	3480	171	2316
SW□2800.40	3040	2562	220	2962	2640	56	39	M36	66	8	10	10	160	0.5	20	3140	154	3264
SW□3150.40	3380	2912	220	3312	2990	64	39	M36	66	8	10	10	160	0.5	22	3498	156	3740
SW□3550.40	3780	3312	220	3712	3390	72	39	M36	66	8	10	10	160	0.5	22	3894	174	4175
SW□4000.40	4240	3762	220	4162	3840	84	39	M36	66	8	10	10	160	0.5	24	4368	179	4801
SW□3150.50	3430	2884	268	3340	2974	56	45	M42	80	8	14	10	190	0.5	24	3552	145	5176
SW□3550.50	3840	3284	268	3740	3374	64	45	M42	80	8	14	10	190	0.5	24	3960	162	5798
SW□4000.50	4290	3734	268	4190	3824	72	45	M42	80	8	14	10	190	0.5	24	4416	181	6544