



131、132型基本系列参数表

基本型号	外形尺寸			安装孔尺寸						结构尺寸			齿轮参数			外齿参数		质量
	D	d	H	D ₁	D ₂	n	通孔	螺蚊孔		n ₁	H ₁	h	b	x	m	da	Z	
							0型	1,2,3型										
							φ	φ	T									
131. 25. 500	634	366	148	598	402	24	18	M16	32	4	138	32	80	0. 5	5	664	130	224
132. 25. 500															6	664. 8	108	
131. 25. 560	694	426	148	658	462	24	18	M16	32	4	138	32	80	0. 5	5	724	142	240
132. 25. 560															6	724. 8	118	
131. 25. 630	764	496	148	728	532	28	18	M16	32	4	138	32	80	0. 5	6	808. 8	132	270
132. 25. 630															8	806. 4	98	
131. 25. 710	844	576	148	808	612	28	18	M16	32	4	138	32	80	0. 5	6	886. 8	145	300
132. 25. 710															8	886. 4	108	
131. 32. 800	964	636	182	920	680	36	22	M20	40	4	172	40	120	0. 5	8	1006. 4	123	500
132. 32. 800															10	1008	98	
131. 32. 900	1064	736	182	1020	780	36	22	M20	40	4	172	40	120	0. 5	8	1102. 4	135	600
132. 32. 900															10	1108	108	
131. 32. 1000	1164	836	182	1120	880	40	22	M20	40	5	172	40	120	0. 5	10	1218	119	680
132. 32. 1000															12	1221. 6	99	
131. 32. 1120	1284	956	182	1240	1000	40	22	M20	40	5	172	40	120	0. 5	10	1338	131	820
132. 32. 1120															12	1341. 6	109	
131. 40. 1250	1445	1055	220	1393	1107	45	26	M24	48	5	210	50	150	0. 5	12	1509. 6	123	1200
132. 40. 1250															14	1509. 2	105	
131. 40. 1400	1595	1205	220	1543	1257	45	26	M24	48	5	210	50	150	0. 5	12	1665. 6	136	1300
132. 40. 1400															14	1663. 2	116	
131. 40. 1600	1795	1405	220	1743	1457	48	26	M24	48	6	210	50	150	0. 5	14	1873. 2	131	1520
132. 40. 1600															16	1868. 8	114	



基本型号	外形尺寸			安装孔尺寸						结构尺寸			齿轮参数			外齿参数		质量
	D	d	H	D ₁	D ₂	n	通孔	螺蚊孔		n ₁	H ₁	h	b	x	m	da	Z	
							0型	1,2,3型										
							φ	φ	T									
131. 40. 1800	1995	1605	220	1943	1657	48	26	M24	48	6	210	50	150	0. 5	14	2069. 2	145	1750
132. 40. 1800															16	2076. 8	127	
131. 45. 2000	2221	1779	231	2155	1845	60	33	M30	60	6	219	54	160	0. 5	16	2300. 8	141	2400
132. 45. 2000															18	2300. 4	125	
131. 45. 2240	2461	2019	231	2395	2085	60	33	M30	60	6	219	54	160	0. 5	16	2556. 8	157	2700
132. 45. 2240															18	2552. 4	139	
131. 45. 2500	2721	2279	231	2655	2345	72	33	M30	60	8	219	54	160	0. 5	18	2822. 4	154	3000
132. 45. 2500															20	2816	138	
131. 45. 2800	3021	2579	231	2955	2645	72	33	M30	60	8	219	54	160	0. 5	18	3110. 4	170	3400
132. 45. 2800															20	3116	153	
131. 50. 3150	3432	2868	270	3342	2958	72	45	M42	84	8	258	65	180	0. 5	20	3536	174	5000
132. 50. 3150															22	3537. 6	158	
131. 50. 3550	3832	3268	270	3742	3358	72	45	M42	84	8	258	65	180	0. 5	20	3936	194	5600
132. 50. 3550															22	3933. 6	176	
131. 50. 4000	4282	3718	270	4192	3808	80	45	M42	84	8	258	65	180	0. 5	22	4395. 6	197	6400
132. 50. 4000															25	4395	173	